



PROFESSIONAL DETAILING PRODUCTS RECIPE FOR A PROPER DETAIL

PRODUCTS:

SOAP: M89 SUPERSUDS/M90 HAWAIIAN SHINE/M91 CHERRY SUDS

SOLVENT: R95 SUPER SOL/R125 CONCENTRATED ORANGE

CLAYBAR: WB4-WB10/Clay Alternatives - We can find the right application for you.

CLAY LUBRICANT: WS1 WONDERSPRAY/SW88 QUICKSPIFF/SW89 BODY GLOSS

WAX: WE WILL SET YOU UP WITH THE PROPER WAX FOR YOUR APPLICATION

STEP 1: Wash your vehicle with soap and water then completely dry the vehicle.

STEP 2: Wipe the vehicle down completely with solvent to remove old wax, tar, grease, and undercoating. Avoid plastic dyed moldings. We suggest wiping around the vehicle one more time with a moist towel.

STEP 3: (OPTIONAL BUT SUGGESTED) Wash the vehicle again to remove any remaining residue from the solvent.

STEP 4: Apply a liberal amount of lubricant to the vehicle's painted surface and with your clay flattened out to the size of your hand, begin to wipe in a back and forth motion on the vehicle paint. Do this around the whole vehicle.

STEP 5: (OPTIONAL BUT SUGGESTED) Wash the vehicle again to remove any remaining residue from the clay bar and lubricant.

STEP 6: Apply wax and remove with microfiber towel

IF YOU HAVE ANY QUESTIONS PLEASE
DON'T HESITATE TO CALL!!!

(330) 454-5105

FIND US
ON FACEBOOK

